



Klemsan®

551018 KKC 6080

60x80 Slotted wiring duct, Grey

General Product Information	Insulating material	PVC - UL 94 V0
Operating Temperature	Minimum Temperature	-15°C
	Maximum Temperature	+60°C
Dimensions	A	60 mm
	B	80 mm
	C	15,8 mm
	D	4 mm
	E	6 mm
	F	2,1 mm
	G	4,5 mm
	H	6,5 mm
	I	25 mm
Length	U	2 Mt.
Product Information	Packing Unit	12x2
	Working range	

Wiring Duct Cutter



- KKMR-Wiring Duct hand cutter for up to 110 mm width and 2,5 mm thick wiring duct.



- KMK 1002-Wiring duct cutter for up to 125 mm width and 2,5 mm thick wiring duct.

Wiring Duct Retainers



Wire retainer

KKT 6080-60x80

Wiring Duct Covers



Wiring duct cover, Grey

KKK 60-60mm

Riveting Tool



mm Plastic Rivet

PPE 6,5 MM-6,5



for rivets

SETR-Setting tool

Clamp For Cable Tie



cable tie

KKB-Clamp for

Cable Holder



KKM-Cable Holder



UL Sertifikası - UL Certificate

Alçak Gerilim direktiflerine uygunluk belgesi - VDE Certificate

Rusya Yangın Sertifikası - Rusya Yangın Sertifikası

Ukrayna Uygunluk Sertifikası - Ukrayna Uygunluk Sertifikası

Avrupa standartlarına uygunluk belgesi - CE Certificate

Türk Standartlarına Uygunluk Belgesi - Wiring Duct TSE certificate

LAPEM - RETIE Sertifikası - LAPEM - Retie Certificate

AutoCat File

Order Info		Dimensions
■	551018 60x80	60x80 Slotted wiring duct,Grey
■	551018WS	60x80 Wide slotted wiring duct,Grey